

CRUNCH SPEAKERS



- Neo-Mylar Soft Dome Tweeter
- UV Resistant Rubber Surround
- Silver Alpha-Cellulose Poly Cone
- Pure Copper Voice Coil
- Kapton Voice Coil Former
- 6dB Internal Passive Butterworth Crossover
- Anti-Resonant Stamped Steel Basket
- Grills Included

CS653 6-1/2" Coaxials • 300w Maximum / 150w RMS

CS693 6 x 9" Coaxials • 400w Maximum / 200w RMS

CRUNCH GTR AMPLIFIERS



- Low Noise Pre-Amp Circuitry
- Versa-Cross Fully Adjustable 24dB Crossovers
- Class A/B Topology
- SPEED-FET MOSFET Output Devices
- Rugged PWM Power Supply
- Includes Bass Remote (Mono Models)
- Full Range Signal Pass-Through
- LED Power & Protect Indicators

GTR3000.1 1 x 750w @ 4Ω 1 x 1500w @ 2Ω 1 x 3000w @ 1Ω

CRUNCH GTRII AMPLIFIERS



- Low Noise Pre-Amp Circuitry
- Versa-Cross Fully Adjustable 12dB Crossovers
- 0-9dB Bass Boost
- Class A/B Topology
- SPEED-FET MOSFET Output Devices
- Rugged PWM Power Supply
- Full Range Signal Pass-Through
- LED Power & Protect Indicators

GTRII1400.4 4 x 175w @ 4Ω 4 x 350w @ 2Ω N/A @ 1Ω

CRUNCH POWER ZONE SUBWOOFERS



- 1.5" Copper wound voice coil
- Vented aluminum coil former
- Reinforced cotton spider
- UV resistant foam surround
- Injection molded polypropylene cone
- Over-coil venting
- Ferrite magnet structure
- Reinforced molded ABS motor cover
- Stamped steel basket

PZX12D4 12" Dual 4Ω Voice Coil • 600w Maximum / 300w RMS